

CONTENTS

		Page	
1	SCOPE	1-1	
	1.1 General	1-1	07
	1.2 Limitations	1-3	
	1.3 Responsibilities	1-3	
	1.4 Documentation Requirements	1-4	
2	REFERENCES	2-1	07
3	DEFINITIONS	3-1	
4	MATERIALS	4-1	
	4.1 General	4-1	07
	4.2 Plates	4-1	
	4.3 Sheets	4-10	
	4.4 Structural Shapes	4-10	
	4.5 Piping and Forgings	4-11	07
	4.6 Flanges	4-12	
	4.7 Bolting	4-12	07
	4.8 Welding Electrodes	4-12	
	4.9 Gaskets	4-12	07
5	DESIGN	5-1	
	5.1 Joints	5-1	07
	5.2 Design Considerations	5-5	
	5.3 Special Considerations	5-8	
	5.4 Bottom Plates	5-9	
	5.5 Annular Bottom Plates	5-9	
	5.6 Shell Design	5-11	07
	5.7 Shell Openings	5-17	
	5.8 Shell Attachments and Tank Appurtenances	5-42	
	5.9 Top and Intermediate Stiffening Rings	5-49	
	5.10 Roofs	5-60	
	5.11 Wind Load on Tanks (Overturning Stability)	5-67	
	5.12 Tank Anchorage	5-68	
6	FABRICATION	6-1	
	6.1 General	6-1	07
	6.2 Shop Inspection	6-1	
7	ERECTION	7-1	
	7.1 General	7-1	07
	7.2 Details of Welding	7-1	
	7.3 Inspection, Testing, and Repairs	7-4	
	7.4 Repairs to Welds	7-7	
	7.5 Dimensional Tolerances	7-8	07
8	METHODS OF INSPECTING JOINTS	8-1	
	8.1 Radiographic Method	8-1	07
	8.2 Magnetic Particle Examination	8-4	
	8.3 Ultrasonic Examination	8-4	
	8.4 Liquid Penetrant Examination	8-5	

	Page	
8.5	Visual Examination	8-5
8.6	Vacuum Testing	8-6
9	WELDING PROCEDURE AND WELDER QUALIFICATIONS.	9-1
9.1	Definitions	9-1
9.2	Qualification of Welding Procedures.	9-1
9.3	Qualification of Welders	9-2
9.4	Identification of Welded Joints	9-2
10	MARKING.	10-1
10.1	Nameplates	10-1
10.2	Division of Responsibility	10-2
10.3	Certification	10-2
APPENDIX A	OPTIONAL DESIGN BASIS FOR SMALL TANKS	A-1
APPENDIX B	RECOMMENDATIONS FOR DESIGN AND CONSTRUCTION OF FOUNDATIONS FOR ABOVEGROUND OIL STORAGE TANKS	B-1
APPENDIX C	EXTERNAL FLOATING ROOFS	C-1
APPENDIX D	TECHNICAL INQUIRIES.	D-1
APPENDIX E	SEISMIC DESIGN OF STORAGE TANKS.	E-1
APPENDIX F	DESIGN OF TANKS FOR SMALL INTERNAL PRESSURES.	F-1
APPENDIX G	STRUCTURALLY-SUPPORTED ALUMINUM DOME ROOFS	G-1
APPENDIX H	INTERNAL FLOATING ROOFS	H-1
APPENDIX I	UNDERTANK LEAK DETECTION AND SUBGRADE PROTECTION	I-1
APPENDIX J	SHOP-ASSEMBLED STORAGE TANKS.	J-1
APPENDIX K	SAMPLE APPLICATION OF THE VARIABLE-DESIGN-POINT METHOD TO DETERMINE SHELL-PLATE THICKNESS	K-1
APPENDIX L	API STD 650 STORAGE TANK DATA SHEET.	L-1
APPENDIX M	REQUIREMENTS FOR TANKS OPERATING AT ELEVATED TEMPERATURES	M-1
APPENDIX N	USE OF NEW MATERIALS THAT ARE NOT IDENTIFIED.	N-1
APPENDIX O	RECOMMENDATIONS FOR UNDER-BOTTOM CONNECTIONS.	O-1
APPENDIX P	ALLOWABLE EXTERNAL LOADS ON TANK SHELL OPENINGS	P-1
APPENDIX R	LOAD COMBINATIONS	R-1
APPENDIX S	AUSTENITIC STAINLESS STEEL STORAGE TANKS.	S-1
APPENDIX T	NDE REQUIREMENTS SUMMARY	T-1
APPENDIX U	ULTRASONIC EXAMINATION IN LIEU OF RADIOGRAPHY.	U-1
APPENDIX V	DESIGN OF STORAGE TANKS FOR EXTERNAL PRESSURE.	V-1
APPENDIX W	COMMERCIAL AND DOCUMENTATION RECOMMENDATIONS	W-1

Figures

4-1	Minimum Permissible Design Metal Temperature for Materials Used in Tank Shells without Impact Testing.	4-6
4-2	Isothermal Lines of Lowest One-Day Mean Temperatures	4-7
4-3	Governing Thickness for Impact Test Determination of Shell Nozzle and Manhole Materials.	4-13
5-1	Typical Vertical Shell Joints	5-2
5-2	Typical Horizontal Shell Joints	5-2
5-3A	Typical Roof and Bottom Joints	5-3
5-3B	Method for Preparing Lap-Welded Bottom Plates under Tank Shell.	5-3

	Page	
5-3C	Detail of Double Fillet-Groove Weld for Annular Bottom Plates with a Nominal Thickness Greater Than 13 mm (1/2 in.)	5-4
5-4	Storage Tank Volumes and Levels	5-7
5-5	Drip Ring (Suggested Detail)	5-9
5-6	Minimum Weld Requirements for Openings in Shells According to 5.7.3	5-18
5-7A	Shell Manhole	5-20
5-7B	Details of Shell Manholes and Nozzles	5-21
5-8	Shell Nozzles (See Tables 5-6, 5-7, and 5-8)	5-22
5-9	Minimum Spacing of Welds and Extent of Related Radiographic Examination	5-30
5-10	Shell Nozzle Flanges (See Table 5-8)	5-34
5-11	Area Coefficient for Determining Minimum Reinforcement of Flush-Type Cleanout Fittings	5-34
5-12	Flush-Type Cleanout Fittings (See Tables 5-9, 5-10, and 5-11)	5-35
5-13	Flush-Type Cleanout-Fitting Supports	5-36
5-14	Flush-Type Shell Connection	5-39
5-15	Rotation of Shell Connection	5-42
5-16	Roof Manholes (See Table 5-13)	5-45
5-17	Rectangular Roof Openings with Flanged Covers	5-48
5-18	Rectangular Roof Openings with Hinged Cover	5-49
5-19	Flanged Roof Nozzles (See Table 5-14)	5-50
5-20	Threaded Roof Nozzles (See Table 5-15)	5-50
5-21	Drawoff Sump (See Table 5-16)	5-51
5-22	Scaffold Cable Support	5-51
5-23	Grounding Lug	5-53
5-24	Typical Stiffening-Ring Sections for Tank Shells (See Table 5-20)	5-54
5-25	Stairway Opening through Stiffening Ring	5-57
5-26	Some Acceptable Column Base Details	5-64
5-27	Overturning Check for Unanchored Tanks	5-67
6-1	Shaping of Plates	6-2
8-1	Radiographic Requirements for Tank Shells	8-2
10-1	Manufacturer's Nameplate	10-1
10-2	Manufacturer's Certification Letter	10-2
B-1	Example of Foundation with Concrete Ringwall	B-3
B-2	Example of Foundation with Crushed Stone Ringwall	B-4
E-1	Coefficient C_i	E-10
F-1	Appendix F Decision Tree	F-2
F-2	Permissible Details of Compression Rings	F-3
G-1	Data Sheet for a Structurally-Supported Aluminum Dome Added to an Existing Tank	G-2
G-2	Typical Roof Nozzle	G-8
I-1	Concrete Ringwall with Undertank Leak Detection at the Tank Perimeter (Typical Arrangement)	I-1
I-2	Crushed Stone Ringwall with Undertank Leak Detection at the Tank Perimeter (Typical Arrangement)	I-2
I-3	Earthen Foundation with Undertank Leak Detection at the Tank Perimeter (Typical Arrangement)	I-2
I-4	Double Steel Bottom with Leak Detection at the Tank Perimeter (Typical Arrangement)	I-3
I-5	Double Steel Bottom with Leak Detection at the Tank Perimeter (Typical Arrangement)	I-3
I-6	Reinforced Concrete Slab with Leak Detection at the Perimeter (Typical Arrangement)	I-4

I-7	Reinforced Concrete Slab with Radial Grooves for Leak Detection (Typical Arrangement)	I-4
I-8	Typical Drawoff Sump	I-5
I-9	Center Sump for Downward-Sloped Bottom	I-5
I-10	Typical Leak Detection Wells	I-6
I-11	Tanks Supported by Grillage Members (General Arrangement)	I-8
O-1	Example of Under-Bottom Connection with Concrete Ringwall Foundation .	O-3
O-2	Example of Under-Bottom Connection with Concrete Ringwall Foundation and Improved Tank Bottom and Shell Support	O-4
O-3	Example of Under-Bottom Connection with Earth-Type Foundation	O-5
P-1	Nomenclature for Piping Loads and Deformation	P-4
P-2A	Stiffness Coefficient for Radial Load: Reinforcement on Shell ($L / 2a = 1.0$) .	P-5
P-2B	Stiffness Coefficient for Longitudinal Moment: Reinforcement on Shell ($L / 2a = 1.0$)	P-5
P-2C	Stiffness Coefficient for Circumferential Moment: Reinforcement on Shell ($L / 2a = 1.0$)	P-6
P-2D	Stiffness Coefficient for Radial Load: Reinforcement on Shell ($L / 2a = 1.5$) .	P-6
P-2E	Stiffness Coefficient for Longitudinal Moment: Reinforcement on Shell ($L / 2a = 1.5$)	P-7
P-2F	Stiffness Coefficient for Circumferential Moment: Reinforcement on Shell ($L / 2a = 1.5$)	P-7
P-2G	Stiffness Coefficient for Radial Load: Reinforcement in Nozzle Neck Only ($L / 2a = 1.0$)	P-8
P-2H	Stiffness Coefficient for Longitudinal Moment: Reinforcement in Nozzle Neck Only ($L / 2a = 1.0$)	P-8
P-2I	Stiffness Coefficient for Circumferential Moment: Reinforcement in Nozzle Neck Only ($L / 2a = 1.0$)	P-9
P-2J	Stiffness Coefficient for Radial Load: Reinforcement in Nozzle Neck Only ($L / 2a = 1.5$)	P-9
P-2K	Stiffness Coefficient for Longitudinal Moment: Reinforcement in Nozzle Neck Only ($L / 2a = 1.5$)	P-10
P-2L	Stiffness Coefficient for Circumferential Moment: Reinforcement in Nozzle Neck Only ($L / 2a = 1.5$)	P-10
P-3A	Construction of Nomogram for b_1, b_2, c_1, c_2 Boundary	P-12
P-3B	Construction of Nomogram for b_1, c_3 Boundary	P-12
P-4A	Obtaining Coefficients Y_F and Y_L	P-13
P-4B	Obtaining Coefficient Y_C	P-14
P-5A	Determination of Allowable Loads from Nomogram: F_R and M_L	P-16
P-5B	Determination of Allowable Loads from Nomogram: F_R and M_C	P-16
P-6	Low-Type Nozzle with Reinforcement in Nozzle Neck Only (for Sample Problem)	P-17
P-7	Allowable-Load Nomograms for Sample Problem	P-19
P-8A	Stress Factor f_R Due to Radial Thrust $F_R, d/t_n = 10$	P-45
P-8B	Stress Factor f_R Due to Radial Thrust $F_R, d/t_n = 30$	P-45
P-8C	Stress Factor f_R Due to Radial Thrust $F_R, d/t_n = 50$	P-46
P-8D	Stress Factor f_R Due to Radial Thrust $F_R, d/t_n = 100$	P-46
P-8E	Stress Factor f_θ Due to Radial Thrust $F_R, d/t_n = 10$	P-47
P-8F	Stress Factor f_θ Due to Radial Thrust $F_R, d/t_n = 30$	P-47
P-8G	Stress Factor f_θ Due to Radial Thrust $F_R, d/t_n = 50$	P-48
P-8H	Stress Factor f_θ Due to Radial Thrust $F_R, d/t_n = 100$	P-48
P-9A	Stress Factor f_r Due to Circumferential Moment $M_C, d/t_n = 10$	P-49
P-9B	Stress Factor f_r Due to Circumferential Moment $M_C, d/t_n = 30$	P-49
P-9C	Stress Factor f_r Due to Circumferential Moment $M_C, d/t_n = 50$	P-50
P-9D	Stress Factor f_r Due to Circumferential Moment $M_C, d/t_n = 100$	P-50

	Page
P-9E	Stress Factor f_{θ} Due to Circumferential Moment M_C , $d/t_n = 10$ P-51
P-9F	Stress Factor f_{θ} Due to Circumferential Moment M_C , $d/t_n = 30$ P-51
P-9G	Stress Factor f_{θ} Due to Circumferential Moment M_C , $d/t_n = 50$ P-52
P-9H	Stress Factor f_{θ} Due to Circumferential Moment M_C , $d/t_n = 100$ P-52
P-10A	Stress Factor f_r Due to Longitudinal Moment M_L , $d/t_n = 10$ P-53
P-10B	Stress Factor f_r Due to Longitudinal Moment M_L , $d/t_n = 30$ P-53
P-10C	Stress Factor f_r Due to Longitudinal Moment M_L , $d/t_n = 50$ P-54
P-10D	Stress Factor f_r Due to Longitudinal Moment M_L , $d/t_n = 100$ P-54
P-10E	Stress Factor f_{θ} Due to Longitudinal Moment M_L , $d/t_n = 10$ P-55
P-10F	Stress Factor f_{θ} Due to Longitudinal Moment M_L , $d/t_n = 30$ P-55
P-10G	Stress Factor f_{θ} Due to Longitudinal Moment M_L , $d/t_n = 50$ P-56
P-10H	Stress Factor f_{θ} Due to Longitudinal Moment M_L , $d/t_n = 100$ P-56
P-11	Stress Reduction Factor P-57
V-1A	Dimensions Self-Supporting Cone Roof V-5
V-1B	Dimensions Self-Supporting Dome Roof V-7

Tables

1-1	Status of Appendices to API Std 650 1-2	07
4-1	Maximum Permissible Alloy Content 4-3	
4-2	Acceptable Grades of Plate Material Produced to National Standards 4-4	
4-3a	Material Groups, SI Units 4-8	
4-3b	Material Groups, US Customary Units 4-9	
4-4	Minimum Impact Test Requirements for Plates (See Note) 4-10	
5-1	Annular Bottom-Plate Thicknesses (t_{br}) 5-10	07
5-2	Permissible Plate Materials and Allowable Stresses 5-12	
5-3	Thickness of Shell Manhole Cover Plate and Bolting Flange 5-19	07
5-4	Dimensions for Shell Manhole Neck Thickness 5-19	
5-5	Dimensions for Bolt Circle Diameter D_b and Cover Plate Diameter D_c for Shell Manholes 5-23	
5-6	Dimensions for Shell Nozzles 5-24	
5-7	Dimensions for Shell Nozzles: Pipe, Plate, and Welding Schedules 5-25	
5-8	Dimensions for Shell Nozzle Flanges 5-26	
5-9	Dimensions for Flush-Type Cleanout Fittings 5-27	
5-10	Minimum Thickness of Cover Plate, Bolting Flange, and Bottom Reinforcing Plate for Flush-Type Cleanout Fittings 5-27	
5-11	Thicknesses and Heights of Shell Reinforcing Plates for Flush-Type Cleanout Fittings 5-27	
5-12	Dimensions for Flush-Type Shell Connections 5-28	
5-13	Dimensions for Roof Manholes 5-46	
5-14	Dimensions for Flanged Roof Nozzles 5-46	
5-15	Dimensions for Threaded Roof Nozzles 5-47	
5-16	Dimensions for Drawoff Sumps 5-51	
5-17	Requirements for Platforms and Walkways 5-52	07
5-18	Requirements for Stairways 5-52	
5-19	Rise, Run, and Angle Relationships for Stairways 5-53	
5-20	Section Moduli (cm^3 [in.^3]) of Stiffening-Ring Sections on Tank Shells 5-55	
5-21a	Uplift Loads (SI Units) 5-69	
5-21b	Uplift Loads (US Customary Units) 5-69	
7-1	Minimum Preheat Temperatures 7-1	
A-1a	Typical Sizes and Corresponding Nominal Capacities (m^3) for Tanks with 1800-mm Courses A-2	07
A-1b	Typical Sizes and Corresponding Nominal Capacities (barrels) for Tanks with 72-in. Courses A-3	

	Page	
A-2a	Shell-Plate Thicknesses (mm) for Typical Sizes of Tanks with 1800-mm Courses	A-4
A-2b	Shell-Plate Thicknesses (in.) for Typical Sizes of Tanks with 72-in. Courses	A-5
A-3a	Typical Sizes and Corresponding Nominal Capacities (m ³) for Tanks with 2400-mm Courses	A-6
A-3b	Typical Sizes and Corresponding Nominal Capacities (barrels) for Tanks with 96-in. Courses	A-7
A-4a	Shell-Plate Thicknesses (mm) for Typical Sizes of Tanks with 2400-mm Courses	A-8
A-4b	Shell-Plate Thicknesses (in.) for Typical Sizes of Tanks with 96-in. Courses	A-9
E-1	Value of F_a as a Function of Site Class	E-7
E-2	Value of F_v as a Function of Site Class	E-7
E-3	Site Classification	E-9
E-5	Importance Factor (I) and Seismic Use Group Classification	E-13
E-4	Response Modification Factors for ASD Methods	E-13
E-6	Anchorage Ratio Criteria	E-18
E-7	Minimum Required Freeboard	E-22
E-8	Design Displacements for Piping Attachments	E-23
G-1	Bolts and Fasteners	G-4
J-1	Maximum Roof Depths for Shop-Assembled Dome-Roof Tanks	J-2
K-1	Shell-Plate Thicknesses Based on the Variable-Design-Point Method Using 2400-mm (96-in.) Courses and an Allowable Stress of 159 MPa (23,000 lbf/in. ²) for the Test Condition	K-9
K-2	Shell-Plate Thicknesses Based on the Variable-Design-Point Method Using 2400-mm (96-in.) Courses and an Allowable Stress of 208 MPa (30,000 lbf/in. ²) for the Test Condition	K-10
K-3	Shell-Plate Thicknesses Based on the Variable-Design-Point Method Using 2400-mm (96-in.) Courses and an Allowable Stress of 236 MPa (34,300 lbf/in. ²) for the Test Condition	K-11
L-1	Index of Decisions or Actions Which may be Required of the Tank Purchaser	L-22
M-1	Yield Strength Reduction Factors	M-2
M-2	Modulus of Elasticity at the Maximum Design Temperature	M-5
O-1	Dimensions of Under-Bottom Connections	O-2
P-1	Modulus of Elasticity and Thermal Expansion Coefficient at the Design Temperature	P-2
P-2	Equations for Stress Factors Due to Radial Thrust F_R	P-26
P-3	Equations for Stress Factors Due to Circumferential Moment M_C	P-27
P-4	Equations for Stress Factors Due to Longitudinal Moment M_L	P-28
P-5	Stress Factors	P-30
P-6	Stress Factors for Sample Problem No. 1	P-34
P-7	Stress Factors for the Reinforcing Plate	P-39
S-1a	ASTM Materials for Stainless Steel Components (SI Units)	S-1
S-1b	ASTM Materials for Stainless Steel Components (US Customary Units)	S-2
S-2	Allowable Stresses for Plate Ring Flanges	S-6
S-3	Allowable Stresses for Plate Ring Flanges	S-6
S-4	Joint Efficiencies	S-6
S-5	Yield Strength Values in MPa (psi)	S-7
S-6	Modulus of Elasticity at the Maximum Design Temperature	S-7
U-1	Flaw Acceptance Criteria for UT Indications May be Used for All Materials	U-4