

AAMA/WDMA/CSA 101/I.S.2/A440-08
**NAFS — North American Fenestration
Standard/Specification for windows,
doors, and skylights**



®Registered trade-mark of
American Architectural
Manufacturers Association



Window & Door Manufacturers Association

®Registered trade-mark of Window & Door
Manufacturers Association



**CANADIAN STANDARDS
ASSOCIATION**

®Registered trade-mark of Canadian Standards Association

American Architectural Manufacturers Association
1827 Walden Office Square, Suite 550
Schaumburg, Illinois
60173-4268 USA
www.aamanet.org
Copyright © American Architectural Manufacturers
Association — 2008

Window & Door Manufacturers Association
1400 East Touhy Avenue, Suite 470
Des Plaines, Illinois
60018 USA
www.wdma.com
Copyright © Window & Door Manufacturers
Association — 2008

Canadian Standards Association
A not-for-profit private sector organization
5060 Spectrum Way, Suite 100
Mississauga, Ontario, Canada
L4W 5N6
1-800-463-6727 • 416-747-4000

*To purchase CSA Standards and related publications, visit
CSA's Online Store at **www.ShopCSA.ca** or call toll-free
1-800-463-6727 or 416-747-4044.*

ISBN 978-1-55436-528-9
Technical Editor: Vanessa Mitchell

© Canadian Standards Association — 2008

Published by AAMA, WDMA, and CSA in January 2008.

All rights reserved. No part of this publication may be reproduced in any form whatsoever without the prior permission of the publisher.

Contents

Preface *vii*

0 Introduction 1

- 0.1 General 1
- 0.1.1 Applicability 1
- 0.1.2 Content 1
- 0.2 Performance classes and levels 2
- 0.2.1 Performance classes 2
- 0.2.2 Guidance for the specifier/purchaser 2
- 0.2.3 Performance grade (PG) designations 2
- 0.2.4 Side-hinged door systems 3
- 0.2.5 Positive and negative design pressure (DP) 3
- 0.2.6 Water penetration resistance testing and performance 4
- 0.2.7 Operation/cycling performance 5
- 0.3 Short-form specification 6

1 Scope 6

- 1.1 General 6
- 1.2 Terminology 7
- 1.3 Units of measurement 7

2 Reference publications 8

3 Definitions 18

4 General requirements 28

- 4.1 General 28
- 4.2 Gateway performance requirements 28
- 4.2.1 General 28
- 4.2.2 Alternative minimum test sizes for Performance Class R products (optional) 28
- 4.3 Performance grades (PG) 29
- 4.3.1 Assignment of performance grade (PG) 29
- 4.3.2 Optional performance grades (PG) 29
- 4.4 Product designations 29
- 4.4.1 General 29
- 4.4.2 Primary designator 32
- 4.4.3 Secondary designator 41
- 4.5 Dual windows or dual doors 44
- 4.5.1 General 44
- 4.5.2 Requirements 45

5 Testing 46

- 5.1 Testing sequence 46
- 5.2 Test specimen requirements 46
- 5.2.1 General 46
- 5.2.2 Composite units and combination assemblies 46
- 5.2.3 Alterations 46
- 5.2.4 Specimen size 47
- 5.2.5 Test specimen installation 47
- 5.3 Testing methods 50
- 5.3.1 Operating force and force to latch 50

- 5.3.2 Air leakage resistance test 54
- 5.3.3 Water penetration resistance test 55
- 5.3.4 Uniform load tests 56
- 5.3.5 Forced-entry resistance test 58
- 5.3.6 Auxiliary (durability) tests 58
- 5.3.7 Condensation resistance (optional) 74
- 5.3.8 Thermal transmittance (optional) 74
- 5.3.9 Acoustical performance (optional) 75
- 5.3.10 Impact performance (optional) 75
- 5.4 Laboratory test report 75

6 Materials 77

- 6.1 Material tolerance 77
- 6.2 Glazing and glass 77
 - 6.2.1 Reference standards 77
 - 6.2.2 General requirements 77
 - 6.2.3 Glazing selection 77
 - 6.2.4 Removable multiple glazing panels 81
 - 6.2.5 Plastic glazing 81
- 6.3 Framing/cladding materials 83
 - 6.3.1 General 83
 - 6.3.2 Wood 83
 - 6.3.3 Wood flush and molded fiber doors 83
 - 6.3.4 Vinyl 84
 - 6.3.5 Cellular PVC 84
 - 6.3.6 Aluminum 85
 - 6.3.7 Fiberglass 85
 - 6.3.8 Steel 86
 - 6.3.9 Cellulosic composite materials 86
 - 6.3.10 Fiber-reinforced PVC 86
 - 6.3.11 Acrylonitrile-butadiene-styrene (ABS) 87
 - 6.3.12 Doorlite insert frame materials 87
 - 6.3.13 Other materials 87

7 Components 88

- 7.1 Hardware 88
 - 7.1.1 General 88
 - 7.1.2 Hung window hardware 88
 - 7.1.3 Casement, awning, hopper, and projected window hardware 88
 - 7.1.4 Door hardware 88
 - 7.1.5 Hinged window hardware 89
 - 7.1.6 Tropical window hardware 89
 - 7.1.7 Dual-action window hardware 90
- 7.2 Fasteners 90
- 7.3 Reinforcing 91
- 7.4 Weatherstrip 91
- 7.5 Insect screens 91
- 7.6 Sealants 92
- 7.7 Coatings/finishes 92
- 7.8 Mullions 92
 - 7.8.1 Mullion rating 92
 - 7.8.2 Composite units 97
 - 7.8.3 Combination assemblies 98
 - 7.8.4 Field mulling without manufacturer's involvement 98

- 7.8.5 Windload deflection 98
- 7.8.6 Operational interference 99
- 7.8.7 Vertical (dead load) deflection 99
- 7.9 Integral ventilating systems/devices 99
- 7.10 Blinds in dual-glazed products 99
- 7.11 Setting blocks 99
- 7.12 Dividers (muntins) 100
 - 7.12.1 True divided lites 100
 - 7.12.2 Simulated divided lites, removable grids, and grills 100

8 Fenestration type and test size 101

- 8.1 General 101
- 8.2 Product dimensions and tolerances 101
 - 8.2.1 Dimensions 101
 - 8.2.2 Tolerances 103
- 8.3 Qualification of designs, configurations, and assemblies 103
 - 8.3.1 General 103
 - 8.3.2 Geometry and components 103
 - 8.3.3 Operation and orientation 104
 - 8.3.4 Composite units and unique framing members 104
- 8.4 Specialty products, basement windows, hinged windows, side lites, and transoms 108
 - 8.4.1 Specialty products 108
 - 8.4.2 Basement windows 108
 - 8.4.3 Hinged windows 109
 - 8.4.4 Side lites and transoms 109

9 Alternative minimum test sizes and minimum performance grades (PG) for selected Class R products (optional) 110

Annexes

- A** (informative) — Contact information for standards development organizations 118

Tables

- 1** — Gateway requirements 28
- 2** — U.S. (only) optional performance grades (PG) 30
- 3** — Canada (only) optional performance grades (PG) 31
- 4** — Optional performance grades (PG) for unit skylights, TDDs, and roof windows 32
- 5** — Product types 36
- 6** — Canadian (only) operating force requirements 51
- 7** — U.S. (only) operating force requirements 52
- 8** — Maximum allowable air leakage 54
- 9** — Canadian (only) air infiltration/exfiltration levels 54
- 10** — Deflection limits for sash/leaf torsion test 61
- 11** — Deflection limits for sash vertical deflection test 62
- 12** — Deflection limits for sash/leaf concentrated load test on latch rail 65
- 13** — Deflection limits for vertical concentrated load test 66
- 14** — Deflection limit for vertical concentrated load test on intermediate frame rails 67
- 15** — Loads for distributed load test 68
- 16** — Loads for stabilizing arm load test 69
- 17** — Load for hold-open arm/stay bar test 70
- 18** — Deflection limits for sash blocked operation test 71
- 19** — Operation/cycling performance (side-hinged door systems) 74
- 20** — Allowable IGU glass loads for Examples 1 and 2 in Clause 6.2.3.3 79
- 21** — Plastic glazing combustibility classes 83

- 22** — Door hardware reference Standards 89
 - 23** — Requirements for fasteners and reinforcing 91
 - 24** — Requirements for exterior finishes 92
 - 25** — Window assembly qualification 107
 - 26** — Alternative minimum test sizes and associated minimum performance grades (PG) for selected Class R products 110
 - 27** — Gateway performance requirements 111
-

Figures

- 1** — Short-form specification 6
- 2** — Primary designator (Example 1) 33
- 3** — Primary designator (Example 2) 34
- 4** — Primary designator (Example 3) 35
- 5** — Product type illustrations 37
- 6** — Examples of specialty products 40
- 7** — Secondary designator (Example 1) 43
- 8** — Secondary designator (Example 2) 44
- 9** — Secondary designator (Example 3) 44
- 10** — Corner sealant detail 47
- 11** — Test specimen mounting 48
- 12** — Set-up for thermoplastic corner weld test 59
- 13** — Set-up for sash/leaf torsion test 60
- 14** — Set-up for sash vertical deflection test 62
- 15** — Perpendicular load for sash/leaf concentrated load test on latch rail 63
- 16** — Parallel load for sash/leaf concentrated load test on latch rail 64
- 17** — Set-up for vertical concentrated load test 66
- 18** — Set-up for vertical concentrated load test on intermediate frame rails 67
- 19** — Set-up for distributed load test 68
- 20** — Set-up for stabilizing arm load test 69
- 21** — Set-up for hold-open arm/stay bar test 70
- 22** — Set-up for awning, hopper, projected hardware load test 71
- 23** — Set-up for unit dead load test 73
- 24** — Test report summary of results 76
- 25** — Mullion types and applications 94
- 26** — Product dimension measurement 102
- 27** — Window assembly qualification — Typical configurations 105
- 28** — Side-hinged door assembly qualification 107